

## IN THE CLAIMS:

Please amend the claims as shown in the Listing of Claims.

### Listing of Claims

1. **(currently amended)** A control pedal assembly comprising, in combination:  
first and second control pedals, each of the first and second control pedals having a first support member, an adjustment member and a second support member;  
a motor connected to the adjustment member and adapted to move the second support member relative to the first support member;  
a sensor located on the second control pedal ~~and receiving an input from only the second control pedal~~, the sensor sensing the movement of the second support member relative to the first support member of the second control pedal; and  
a controller member in communication with the sensor to receive signals from the sensor, wherein the controller member is adapted to stop power to the motor when signals from the sensor indicate that the second support member is not moving relative to the first member while power is provided to the motor;  
wherein the sensor is located away from the motor and near the adjustment member.

2. **(original)** The control pedal assembly as claimed in 1, wherein the controller member moves the second support member to a predetermined position when predetermined conditions are met.

3. **(original)** The control pedal assembly as claimed in claim 2, wherein the predetermined conditions include one of an ignition switch turned off, an open door, trunk lid open, a manual switch and a memory device.

4. **(original)** The control pedal assembly as claimed in claim 2, wherein the predetermined position is a forward position.

5. **(original)** The control pedal assembly as claimed in claim 1, wherein the controller member further includes a control device in communication with the controller member and

adapted to prevent movement of the second support member relative to the first support member when engaged.

102 ✓ 6. **(original)** The control assembly as claimed in claim 1, wherein the controller member is adapted to automatically move the second support member in a forward direction relative to the first support member to a predetermined position when predetermined conditions are met.

7. **(previously presented)** The control pedal assembly as claimed in claim 1, further comprising, in combination:

103 ✓ a second sensor located on the other of the pair of control pedals and located away from the motor, the controller member is adapted to determine the position of each of the pair of control pedals based on signals from the sensors to automatically stop the motor when a predetermined fore-aft relationship between the one and other of the pair of control pedals has not been maintained.

cl 8. **(currently amended)** A control pedal assembly comprising, in combination:

first and second control pedals, each control pedal comprising a first support, a screw secured to the first support, a nut threadably engaging the screw and adapted to axially move along the screw upon rotation of the screw, and a second support operatively connected to the nut for fore-aft movement of the second support relative to the first support upon axial movement of the nut along the screw; and

103 ✓ a control system including at least one motor operatively connected to the screws to selectively rotate the screws and axially move the nuts along the screws, a rotational sensor carried by one of the first control pedal and the second control pedal, and a controller in communication with the sensor to receive signals pulses from the sensor;

wherein each of the pulses from the sensor indicates a predetermined amount of rotation of the screw: P p P0039 Hall effect sensor.

wherein the rotational sensor is located away from the motor and near the screw.

103 9. **(currently amended)** The control pedal assembly as claimed in claim 8, wherein the controller is adapted to automatically stop the motor when ~~signals~~ a lack of the pulses from the sensor indicates that ~~at least one of the motor and the screw~~ is not rotating.

10. **(currently amended)** A control pedal comprising, in combination:  
a first support;  
a screw secured to the first support;  
a nut threadably engaging the screw and adapted to move axially along the screw upon rotation of the screw;  
a motor operatively connected to the screw to selectively rotate the screw;  
102 a second support operatively connected to the nut for fore-aft movement of the second support relative to the first support upon axial movement of the nut along the screw; and  
a control system including a sensor adjacent one of the first support and the second support ~~and receiving input from only the control pedal~~, to sense movement of the second support relative to the first support and a controller in communication with the sensor to receive signals from the sensor;  
wherein the sensor is spaced-apart from the motor.

102 11. **(original)** The control pedal according to claim 10, wherein the sensor is selected from the group of a Hall effect device, an inductance sensor, a potentiometer, and an encoder.

102 12. **(original)** The control pedal according to claim 10, wherein the controller is adapted to determine a position of the second support relative to the first support based on signals from the sensor and to automatically stop the motor when the second support reaches a predetermined position relative to the first support.

102 13. **(original)** The control pedal according to claim 12, wherein the controller is adapted to determine a position of the second support based on signals from the sensor and to automatically stop the motor when the second support reaches a desired end of travel relative to the first support.

102 14. **(original)** The control pedal according to claim 10, wherein the controller is adapted to automatically stop the motor when signals from the sensor indicate that the second support is not moving relative to the first support.

102 15. **(original)** The control pedal according to claim 10, wherein the controller is adapted to automatically move the second support in a forward direction relative to the first support to a predetermined position when predetermined conditions are met.

102 16. **(original)** The control pedal according to claim 10, wherein the control system further includes a control device in communication with the controller and adapted to prevent movement of the second support relative to the first support when engaged.

103 17. **(previously presented)** The control pedal according to claim 10, wherein the sensor senses rotation of the screw.

102 18. **(original)** The control pedal assembly according to claim 10, wherein one of the first support and the second support carrying a pedal.

19. **(currently amended)** A control pedal comprising, in combination:

a first support;

a screw secured to the first support;

102 a nut threadably engaging the screw and adapted to move axially along the screw upon rotation of the screw;

a motor operatively connected to the screw to selectively rotate the screw and axially move the nut along the screw;

a second support operatively connected to the nut for fore-aft movement of the second support relative to the first support upon axial movement of the nut along the screw;

a sensor located to directly sense the movement of the first support relative to the second support; and

a controller in communication with the sensor to receive signals from the sensor, wherein the controller is adapted to automatically stop power to the motor when signals from the sensor

indicate that the first support is not moving relative to the second support while power is provided to the motor.

102 20. **(previously presented)** The control pedal according to claim 19, wherein the sensor is a rotational sensor and is located near one of the first support and the second support to sense relative rotational movement therebetween.

21. **(currently amended)** A control pedal assembly comprising, in combination:  
first and second control pedals, each control pedal including a first support, a screw secured to the first support, a nut threadably engaging the screw and adapted to axially move along the screw upon rotation of the screw, and a second support operatively connected to the nut for fore-aft movement of the second support relative to the first support upon axial movement of the nut along the screw; and

21  
a control system including at least one motor operatively connected to the screws of the first support and the second support to selectively rotate the screws and axially move the nuts along the screws, a sensor carried by one of the first control pedal and the second control pedal ~~and receiving input from only one of the first and second control pedals~~ to sense rotation of the screw of one of the first control pedal and the second control pedal, and a controller in communication with the sensor to receive ~~signals~~ pulses from the sensor;

103  
wherein each of the pulses from the sensor indicates a predetermined amount of rotation of the screw;

wherein the screws of the first and second control pedals are operatively connected to the motor in series such that the screw of the second control pedal is connected to the motor and the screw of the first control pedal is connected to the screw of the second control pedal;

wherein the sensor is spaced-apart from the motor and located near one of the screws connected in series.

107 22. **(currently amended)** The control pedal assembly according to claim 21, wherein the control system includes another sensor located near the other one of the screws connected in series, the controller is in communication with the another sensor to receive pulses from the

another sensor, and each of the pulses from the another sensor indicates a predetermined amount of rotation of the screw.

23. **(currently amended)** A control pedal assembly comprising, in combination:

first and second control pedals, each control pedal including a first support, a screw secured to the first support, a nut threadably engaging the screw and adapted to axially move along the screw upon rotation of the screw, and a second support operatively connected to the nut for fore-aft movement of the second support relative to the first support upon axial movement of the nut along the screw; and

(02) a control system including at least one motor operatively connected to the screws to selectively rotate the screws and axially move the nuts along the screws, a sensor located adjacent to one of the second control pedal and the first control pedal ~~and receiving input from only one of the first control pedal and the second control pedal~~, and a controller in communication with the sensor to receive the signals from the sensor, wherein the controller is adapted to determine the position of the second support relative to the first support based on the signals from the sensor and to automatically stop the motor when the position of the second support relative to the first support indicates that a predetermined fore-aft relationship between the first and the second control pedals has not been maintained.

(02) 24. **(previously presented)** The control pedal assembly according to claim 23, wherein the sensor is at least partially secured to one of the first adjustable control pedal and the second adjustable control pedal for movement therewith.

(02) 25. **(original)** The control pedal assembly according to claim 23, wherein the sensor is selected from the group of a Hall effect device, an inductance sensor, a potentiometer, and an encoder.

(03) 26. **(original)** The control pedal assembly according to claim 23, wherein the sensor is located near the screw of one of the first adjustable control pedal and the second adjustable control pedal, to directly sense rotation of the screw.

27. (cancelled)

28. (cancelled)

29. (cancelled)

30. (cancelled)

31. (cancelled)

32. (original) A control pedal comprising, in combination:

a first support;

a screw secured to the first support;

a nut threadably engaging the screw and adapted to axially move along the screw upon rotation of the screw;

a second support operatively connected to the nut for fore-aft movement of the second support relative to the first support upon axial movement of the nut along the screw;

a sensor adjacent to one of the first support and second support;

a motor operatively connected to the screw to selectively rotate the screw and axially move the nut along the screw; and

a controller in communication with the motor and the sensor and adapted to automatically operate the motor to move the second support in a forward direction relative to the first support to a predetermined position when predetermined conditions are met;

wherein the predetermined conditions includes at least one of an ignition switch turned off and an open door.

33. (original) The control pedal according to claim 32, wherein the predetermined position is a full forward position.

34. (original) The control pedal according to claim 33, wherein the predetermined conditions include both an ignition switch turned off and an open door.

35. **(original)** The control pedal according to claim 32, wherein the predetermined conditions include both an ignition switch turned off and an open door.

C/ 36. **(cancelled)**

---